



NINGBO HONGWEI INTERNATIONAL TRADE CO.,LTD
No.419 Xinwang Dasha Jishigang Yinzhou Ningbo China 315171

TECHNICAL DATA SHEET

Product: -PVC plain weave double side coated Fabric (7704) Blockout, with both lacquered. UV Treated, Anti Fungus.

Application:

Support Cloth (DIN 6000)	Polyester
Specification (DIN EN 1049-2)	23*23 per inch(plain weave)
Yarn (dtex) (DIN EN ISO 2060)	1000*1000 D
Type of Coating	pvc coated on both sides
Total Weight (DIN EN ISO 2286-2)	800g/m ²
Width (DIN EN ISO 2286-1)	UP TO 3.2M
Tensile strength (DIN 53354)	3500/3400 N/5CM
Tear strength (DIN 53356)	360/340 N/5CM
Adhesion Strength	100N/5CM
Low Temperature-No Crack At	-30°C to +70°C
Flame Retardant	NFPA701,M2,B1

Tents, Pergola roofing

Packing: craft paper or PE foam Features:

A: UV resistant , FR (NFPA701,B1,M2

B: Cold resistant, Anti-Mildow

C: Glossy and Matt surface

D: Lacquered are available as requests

E: Color, weight can be customized